












Our profiles at a glance

HORNSEY STEEL PANELS AND SECTIONS LTD

Profile	Recommended Application		Gauge	Finish	Scan or click QR code for further info
 20/1000 Liner	ROOF	 Forward Rolled • Cover Width 1000mm	0.7mm	20/5µm Commercial Liner 25/10µm Poultry Liner	 Profile Height: 20mm Profile Pitch: 200mm Curving Available: Yes Length: 500mm to 9000mm
	WALL	 Reverse Rolled • Cover Width 1000mm	0.4mm		
 32/1000	ROOF	 Forward Rolled • Cover Width 1000mm	0.7mm	25/10µm Polyester 35/10µm Wrinkle Polyester LG200µm Standard Plastisol LG200µm Accent Plastisol PP40y 200µm Plastisol PU40 Metallic Silver Galvanised & Corten Colorcoat HPS200 Ultra®	 Profile Height: 32mm Profile Pitch: 200mm Curving Available: Yes Length: 500mm to 15000mm
	WALL	 Reverse Rolled • Cover Width 1000mm	0.5mm		
 32/1000XP Increased Load Bearing Capability	ROOF	 Forward Rolled • Cover Width 1000mm	0.7mm	25/10µm Polyester 35/10µm Wrinkle Polyester LG200µm Standard Plastisol LG200µm Accent Plastisol PP40y 200µm Plastisol PU40 Metallic Silver Galvanised & Corten Colorcoat HPS200 Ultra®	 Profile Height: 32mm Profile Pitch: 200mm Curving Available: Yes Length: 500mm to 15000mm
	WALL	 Reverse Rolled • Cover Width 1000mm	0.5mm		
 34/1000	ROOF	 Forward Rolled • Cover Width 1000mm	0.7mm	25/10µm Polyester 35/10µm Wrinkle Polyester LG200µm Standard Plastisol LG200µm Accent Plastisol PP40y 200µm Plastisol PU40 Metallic Silver Galvanised & Corten Colorcoat HPS200 Ultra®	 Profile Height: 34mm Profile Pitch: 167mm Curving Available: Yes Length: 500mm to 15000mm
	WALL	 Reverse Rolled • Cover Width 1000mm	0.5mm		
 8/3"	ROOF	 Forward Rolled • Cover Width 601mm	0.5mm	Galvanised	 Profile Height: 19mm Profile Pitch: 76mm Curving Available: No Length: 500mm to 6000mm
	WALL	 Forward Rolled • Cover Width 601mm	0.5mm		
 10/3"	ROOF	 Forward Rolled • Cover Width 762mm	0.7mm	LG200µm Standard Plastisol (Only available in 0.7mm Juniper Green & Jet Black) Galvanised	 Profile Height: 19mm Profile Pitch: 76mm Curving Available: Yes Length: 500mm to 9000mm
	WALL	 Forward Rolled • Cover Width 762mm	0.5mm		
 13.5/3"	ROOF	 Forward Rolled • Cover Width 990mm	0.7mm	25/10µm Polyester 35/10µm Wrinkle Polyester LG200µm Standard Plastisol LG200µm Accent Plastisol PP40y 200µm Plastisol PU40 Metallic Silver Galvanised & Corten Colorcoat HPS200 Ultra®	 Profile Height: 19mm Profile Pitch: 76mm Curving Available: Yes Length: 500mm to 12000mm
	WALL	 Forward Rolled • Cover Width 990mm	0.5mm		
 32/1000 Box Tile	ROOF	 Forward Rolled • Cover Width 1000mm Side View: 	0.5mm	25/10µm Polyester 35/10µm Wrinkle Polyester LG200µm Standard Plastisol Galvanised	 Profile Height: 32mm Profile Pitch: 200mm Curving Available: No Length: 750mm to 7500mm
 33/1000 Pan Tile	ROOF	 Forward Rolled • Cover Width 1000mm Side View: 	0.5mm 0.7mm	25/10µm Polyester 35/10µm Wrinkle Polyester LG200µm Standard Plastisol LG200µm Accent Plastisol PP40y 200µm Plastisol PU40 Metallic Silver Galvanised Colorcoat HPS200 Ultra®	 Profile Height: 33mm Profile Pitch: 200mm Curving Available: No Length: 750mm to 7500mm

ANTIDROP CONDENSATION CONTROL

A layer of Antidrop anti-condensation felt membrane can be applied to the reverse of the sheet during manufacturing to help control condensation. Available on all of our profiles except the 8/3", 10/3" and 20/1000 - please enquire for further info.

All dimensions given may be subject to a standard manufacturing tolerance of +/- 5mm

LINER SHEET OPTIONS

Along with our 20/1000 standard liner sheet, the following profiles are also available in 0.4mm and 0.7mm 20/5µm Commercial Liner - 32/1000, 32/1000XP, 34/1000 & 13.5/3".

Version HSPASCOLOURS&FINISHES 1.0 SK 03/26

Colours & Finishes



- A 20/5µm Commercial Liner**
Available for HSPAS 20/1000 (0.4mm & 0.7mm), HSPAS 32/1000 & XP (0.4mm & 0.7mm), HSPAS 34/1000 (0.4mm & 0.7mm), and HSPAS 13.5/3" (0.4mm & 0.7mm).
- B Poultry Liner**
Available for HSPAS 20/1000 (0.4mm), HSPAS 32/1000 + XP (0.4mm), and HSPAS 34/1000 (0.4mm).
- C 25/10µm Polyester**
Available for HSPAS 32/1000 + XP (0.5mm & 0.7mm), HSPAS 32/1000 Box Tile (0.5mm), HSPAS 33/1000 Pan Tile (0.5mm & 0.7mm), HSPAS 34/1000 (0.5mm & 0.7mm) and HSPAS 13.5/3" (0.5mm & 0.7mm).
- D 35/10µm Wrinkle Polyester**
Available for HSPAS 32/1000 + XP (0.5mm & 0.7mm), HSPAS 32/1000 Box Tile (0.5mm), HSPAS 33/1000 Pan Tile (0.5mm & 0.7mm), HSPAS 34/1000 (0.5mm & 0.7mm) and HSPAS 13.5/3" (0.5mm & 0.7mm).
- E LG200µm Standard Plastisol**
Available for HSPAS 32/1000 & XP (0.5mm & 0.7mm), HSPAS 32/1000 Box Tile (0.5mm), HSPAS 33/1000 Pan Tile (0.5mm & 0.7mm), HSPAS 34/1000 (0.5mm & 0.7mm), HSPAS 34/667 (0.7mm), HSPAS 10/3" (Only available in 0.7mm Juniper Green & Jet Black) and HSPAS 13.5/3" (0.5mm & 0.7mm).
- F LG200µm Accent Plastisol**
Available for HSPAS 32/1000 & XP (0.7mm), HSPAS 33/1000 Pan Tile (0.7mm), HSPAS 34/1000 (0.7mm) and HSPAS 13.5/3" (0.7mm).
- G PP40y 200µm Goosewing Grey**
Available for HSPAS 32/1000 & XP (0.7mm), HSPAS 34/1000 (0.7mm), HSPAS 33/1000 Pan Tile (0.7mm) and HSPAS 13.5/3" (0.7mm).
- H Premium PU40 Metallic Silver**
Available for HSPAS 32/1000 & XP (0.7mm), HSPAS 33/1000 Pan Tile (0.7mm), HSPAS 34/1000 (0.7mm) and HSPAS 13.5/3" (0.7mm).
- I Galvanised** - Mill Finish
Available for all profiles in 0.5mm & 0.7mm except: HSPAS 20/1000.
- J Corten** - Mill Finish
Available for all profiles in 0.8mm except: HSPAS 20/1000, HSPAS 32/1000 Box Tile, HSPAS 33/1000 Pan Tile, HSPAS 34/667, HSPAS 8/3" and HSPAS 10/3".
- Colorcoat HPS200 Ultra®** by Tata Steel is available on special order, there may be a slightly increased lead time. Colorcoat® and Colorcoat HPS200 Ultra® are trademarks of Tata Steel UK.
- The BS (British Standard) and RAL colour codes are the closest colours and are not an exact match to the actual product itself.

We also manufacture and supply:

Custom made roof flashings, gutters and accessories · Bespoke pressed profiled sheets
Unique fabrications, fascias, trims and fixings · Purlins and sections including Zed purlins, Cee sections, Flat Faced and Recessed Eaves beams and accessories · MasterBar and bracket roof and wall spacer system · Insulated composite panels and rooflights
Fibre Cement Sheets · Cladding Mat 40 Superglass Insulation · FloPlast Ltd Xtraflo rainwater products.

The colours shown here are for guidance only, for an accurate representation please contact us for a physical sample.

Galvanised I	Corten (Weathered) J	Bright White BS 00E55 RAL 9003 A B	Pure White BS 10A01 RAL 9010 C E	
Silver BS 00E55 RAL 9006 H	Goosewing Grey BS 10A05 RAL 7038 B C E G	Mushroom BS 10B19 RAL 080 70 10 F	Navy Blue BS 7086 RAL 5003 F	Slate Blue BS 18B29 RAL 6008 C E
Ivory BS 00A01 RAL 9002 F	Anthracite Grey BS 9098 RAL 7016 C D E	Cornflower Blue BS 18E53 RAL 240 40 40 F	Wedgewood Blue BS 18C37 RAL 220 50 15 F	Poppy Red BS 04E53 RAL 2002 F
Jet Black BS 00E53 RAL 9005 C D E	Merlin Grey BS 18B25 RAL 180 40 05 C E	Pigeon Grey BS 18B17 RAL 7035 F	Ocean Blue BS 18C39 RAL 220 30 25 F	Terracotta Red BS 04C39 RAL 040 40 40 E
Juniper Green BS 12B29 RAL 140 20 10 C D E	Olive Green BS 12B27 RAL 100 30 20 C E	Moorland Green BS 12B21 RAL 100 80 20 E	Forest Green BS 225 RAL 6002 F	Vandyke Brown BS 08B29 RAL 8014 E

A 20/5µm Commercial Liner Appearance: Smooth Gauge (Thickness): 0.4mm & 0.7mm Top Coat Thickness: 20 microns Material: Alloy coated steel Usage: Internal Warranty Period: Not applicable	B 25/10µm Poultry Liner Appearance: Smooth Gauge (Thickness): 0.4mm Top Coat Thickness: 25 microns Material: Alloy coated steel Usage: Internal Warranty Period: Not applicable	C 25/10µm Polyester Appearance: Smooth Gauge (Thickness): 0.5mm & 0.7mm Top Coat Thickness: 25 microns Material: Alloy coated steel Usage: External Warranty Period: Not applicable	D 35/10µm Wrinkle Polyester Appearance: Wrinkle texture Gauge (Thickness): 0.5mm & 0.7mm Top Coat Thickness: 35 microns Material: Alloy coated steel Usage: External Warranty Period: Up to 15 years	E & F LG200µm Standard Plastisol & LG200µm Accent Plastisol Appearance: Leathergrain texture Gauge (Thickness): 0.5mm & 0.7mm Top Coat Thickness: 200 microns Material: Alloy coated steel Usage: External Warranty Period: Up to 30 years
G PP40y 200µm Plastisol Appearance: Embossed Gauge (Thickness): 0.7mm Top Coat Thickness: 200 microns Material: Alloy coated steel Usage: External Warranty Period: Up to 40 years	H Premium PU40 Metallic Silver Appearance: Smooth metallic Gauge (Thickness): 0.7mm Top Coat Thickness: 60 microns Material: Alloy coated steel Usage: External Warranty Period: Up to 40 years	I Galvanised Appearance: Smooth mill finish Gauge (Thickness): 0.5mm & 0.7mm Top Coat Thickness: Uncoated Material: Alloy coated steel Usage: External Warranty Period: Not applicable	J Corten Appearance: Smooth mill finish Gauge (Thickness): 0.8mm Top Coat Thickness: Uncoated Material: Steel Alloy Usage: External Warranty Period: Not applicable	Colorcoat HPS200 Ultra® Appearance: Embossed Gauge (Thickness): 0.5mm & 0.7mm Coating Thickness: 200 microns Material: Galvalloy® Metallic Coating Usage: External Available on special order Warranty Period: Up to 40 years

Warranties on all applicable products must be applied for in writing at time of order.